



Ø Mandrins	A	B	C	P	S	V	Y	Z	d1	références sur stock		références sur demande	
										3 mors	3 M fraisés 120°	4 mors	4 M fraisés 90°

pour mandrins AUTOBLOK : pas des stries 1/16 à 90°

hauteurs normales

125	30	30	70	1/16-90°	4	12	15	16	9	1403160053C00	1403160053C15	1403160054C00	1403160054C40
170	35	35	70	1/16-90°	5	14	16	16	11	1403250053C00	1403250053C15	1403250054C00	1403250054C40
200	40	40	90	1/16-90°	5	17	20	23	13	1403310053C00	1403310053C15	1403310054C00	1403310054C40
250	45	45	110	1/16-90°	6	21	20	30	17	1403410053C00	1403410053C15	1403410054C00	1403410054C40
315	50	50	125	1/16-90°	6	21	22	30	17	1403540053C00	1403540053C15	1403540054C00	1403540054C40
400	60	60	140	1/16-90°	6	21	25	34	17	1403710053C00	1403710053C15	1403710054C00	1403710054C40
500 - 630	60	60	160	3/32-90°	6	28	25	38	21	1403730053C00	1403730053C15	1403730054C00	1403730054C40

hauteurs spéciales B1

125	28	48	70	1/16-90°	4	12	15	16	9	1403160053C11	1403160053C20	1403160054C11	1403160054C45
170	35	58	70	1/16-90°	5	14	16	16	11	1403250053C11	1403250053C20	1403250054C11	1403250054C45
200	38	58	90	1/16-90°	5	17	20	23	13	1403310053C11	1403310053C20	1403310054C11	1403310054C45
250	45	58	110	1/16-90°	6	21	20	30	17	1403410053C11	1403410053C20	1403410054C11	1403410054C45
315	48	78	125	1/16-90°	6	21	22	30	17	1403540053C11	1403540053C20	1403540054C11	1403540054C45

hauteurs spéciales B2

170	35	78	70	1/16-90°	5	14	16	16	11	1403250053C12	1403250053C25	1403250054C12	1403250054C50
200	38	78	90	1/16-90°	5	17	20	23	13	1403310053C12	1403310053C25	1403310054C12	1403310054C50
250	45	78	110	1/16-90°	6	21	20	30	17	1403410053C12	1403410053C25	1403410054C12	1403410054C50

hauteurs spéciales B3

250	45	98	110	1/16-90°	6	21	20	30	17	1403410053C13	1403410053C30	1403410054C13	1403410054C55
-----	----	----	-----	----------	---	----	----	----	----	---------------	---------------	---------------	---------------

Ø Mandrins	A	B	C	P	S	V	Y	Z	d1	références sur stock		références sur demande	
										3 mors	3 M fraisés 120°	4 mors	4 M fraisés 90°

pour mandrins FORKARDT type WB : pas des stries 1/16 à 90°

160	WB11/70	39	58	70	1/16-90°	4	17	15	22	13	1412230053E00	1412230053E15	1412230054E00	1412230054E40
200	WB11/90	39	58	90	1/16-90°	4	17	25	22	13	1412310053E00	1412310053E15	1412310054E00	1412310054E40
250-315	WB12	49	78	120	1/16-90°	4	21	30	28	17	1412410053E00	1412410053E15	1412410054E00	1412410054E40
315 AM	WB13	59	88	140	1/16-90°	5	25,5	30	35	21	1412540053E00	1412540053E15	1412540054E00	1412540054E40
400-500	WB23	59	88	155	3/32-90°	5	25,5	30	35	21	1412710053E00	1412710053E15	1412710054E00	1412710054E40

pour mandrins FORKARDT type 2 BLE : pas des stries 1/16 à 90°

200	type BLE	68	67	95	1/16-90°	5	21	22	27	17	1412310152E00			
250	type BLE	68	67	110	1/16-90°	5	25,5	20	35	21	1412410152E00			
315	type BLE	78	77	125	1/16-90°	5	25,5	28	35	21	1412540152E00			
400	type BLE	78	77	150	1/16-90°	5	25,5	28	35	21	1412710152E00			
500	type BLE	78	77	150	1/16-90°	5	25,5	28	35	21	1412710152E00			