



Ø Mandrins	A	B	C	D	E	F	G	références sur stock		références sur demande	
								3 mors	3 M fraisés 120°	4 mors	4 M fraisés 90°
<i>longueurs spéciales C1</i>											
100	14	38	60	6	7,2	5,8	5,5	1320110013A07	1320110013A16	1320110014A07	1320110014A41
125	18	43	70	8	10	7	6,5	1320160013A07	1320160013A16	1320160014A07	1320160014A41
160	20	48	80	9	12	8	7	1320230013A07	1320230013A16	1320230014A07	1320230014A41
200-215	23	58	100	10	14	9	9	1320310013A07	1320310013A16	1320310014A07	1320310014A41
250	25	68	125	12	15	10	9	1320410013A07	1320410013A16	1320410014A07	1320410014A41
300	28	78	150	13	17	10	9	1320510013A07	1320510013A16	1320510014A07	1320510014A41
315	33	78	150	13	19	10	9	1320540013A07	1320540013A16	1320540014A07	1320540014A41
350-400	37	88	175	14	21	11	10	1320710013A07	1320710013A16	1320710014A07	1320710014A41
500	48	98	220	15	31	13	12	1320730013A07	1320730013A16	1320730014A07	1320730014A41
<i>longueurs spéciales C2</i>											
160	20	48	100	9	12	8	7	1320230013A08	1320230013A17	1320230014A08	1320230014A42
200-215	23	58	125	10	14	9	9	1320310013A08	1320310013A17	1320310014A08	1320310014A42
250	25	68	150	12	15	10	9	1320410013A08	1320410013A17	1320410014A08	1320410014A42
300	28	78	180	13	17	10	9	1320510013A08	1320510013A17	1320510014A08	1320510014A42
315	33	78	180	13	19	10	9	1320540013A08	1320540013A17	1320540014A08	1320540014A42
350-400	37	88	220	14	21	11	10	1320710013A08	1320710013A17	1320710014A08	1320710014A42
500	48	98	260	15	31	13	12	1320730013A08	1320730013A17	1320730014A08	1320730014A42
<i>longueurs spéciales C3</i>											
200-215	23	58	150	10	14	9	9	1320310013A09	1320310013A18	1320310014A09	1320310014A43
250	25	68	175	12	15	10	9	1320410013A09	1320410013A18	1320410014A09	1320410014A43
300	28	78	220	13	17	10	9	1320510013A09	1320510013A18	1320510014A09	1320510014A43
315	33	78	220	13	19	10	9	1320540013A09	1320540013A18	1320540014A09	1320540014A43
350-400	37	88	260	14	21	11	10	1320710013A09	1320710013A18	1320710014A09	1320710014A43
500	48	98	300	15	31	13	12	1320730013A09	1320730013A18	1320730014A09	1320730014A43
<i>longueurs spéciales C4</i>											
200-215	23	58	170	10	14	9	9	1320310013A10	1320310013A19	1320310014A10	1320310014A44
315	33	78	260	13	19	10	9	1320540013A10	1320540013A19	1320540014A10	1320540014A44
350-400	37	88	300	14	21	11	10	1320710013A10	1320710013A19	1320710014A10	1320710014A44
500	48	98	350	15	31	13	12	1320730013A10	1320730013A19	1320730014A10	1320730014A44